



NOTES:

1. TOPSOIL TO BE REMOVED TO ITS FULL DEPTH ALONG ENTIRE WIDTH OF ROAD BETWEEN CURBS.
2. BOULEVARD TO BE FULLY SODDED AS SPECIFIED.
3. ROAD RECONSTRUCTION DESIGN TO BE CONFIRMED BY GEOTECHNICAL DESIGN. SUBDRAIN TO BE PROVIDED BASED ON MUNICIPAL STANDARDS AND GEOTECHNICAL RECOMMENDATIONS.
4. ROAD CROSSINGS DEPTHS FOR UTILITIES - HYDRO 1.2 MIN.
- BELL TELEPHONE, UNION GAS, CABLE TV 1.0 MIN.
- WATER 1.8 MIN.
5. ALL WATER SERVICE BOXES TO BE SET AT THE PROPERTY LINE.
6. SIDEWALK TO BE ON ONE SIDE IN RESIDENTIAL AREAS.
7. TRANSFORMER TO BE ON OPPOSITE SIDE TO SIDEWALK WHERE POSSIBLE.



**Township of
North Huron**

**Typical 20 meter Urban Subdivision
Section and Service Locations
Local Residential Streets**

DATE OF REVISION - Jun. 14, 2018

